

# Proving Water Pipe MODEL : PP-1

## GENERAL DESCRIPTION

The water supplies proving equipment is designed to provide the facility to test the rate of flow and pressure of the water supply available to sprinkler installations controlling valves covering a variety of hazard groups. The proving pipe is provided with a flow gauge and orifice plate available as a matched set, one for each hazard group.

## FEATURES

- No specialized knowledge in the use of this equipment is required. A leaflet is enclosed with each product giving easy to follow instructions and details of operating parameters.
- Robust corrosion resistant design.
- Flow gauges are calibrated to the hazard class group required.
- Proving pipe is designed to avoid blocking, removing doubts of inaccurate readings.

## AREAS OF INSTALLATION

The water supplies proving pipe can be used for Wet, Dry and Alternate applications to BS 5306 Pt 2 to hazard groups OH1, OH2, OH3 and OH3S.

**Caution:** When using a water supplies proving pipe, the drain pipework downstream of the orifice plate must have a friction loss less than 30 mb.

## WARRANTY

Products are guaranteed against defects in material or workmanship for one year from delivery.



## ORDERING INFORMATION

Water Supplies proving equipment can be ordered as per hazard group.

**Hazard Group**  
( Available in )

OH1  
OH2  
OH3

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND OTHER INFORMATION INCLUDED IN THIS CATALOGUE WITHOUT NOTICE.

DISTRIBUTED BY :